

## Infrastructure - Story #1129

### Tomcat needs to be configured to handle \ in URIs

2010-12-02 23:01 - Chad Berkley

<b>Status:</b> Closed	<b>Start date:</b> 2010-12-02
<b>Priority:</b> High	<b>Due date:</b>
<b>Assignee:</b>	<b>% Done:</b> 100%
<b>Category:</b>	<b>Estimated time:</b> 0.00 hour
<b>Target version:</b> Sprint-2010.50	
<b>Story Points:</b>	
<b>Description</b>	
Tomcat doesn't like \ or its escaped representation (%5C), for security reasons related to proxying. <a href="http://tomcat.apache.org/security-6.html#Fixed_in_Apache_Tomcat_6.0.10">http://tomcat.apache.org/security-6.html#Fixed_in_Apache_Tomcat_6.0.10</a> (the current encoding specification we use escapes \ to %5C)	
<b>Subtasks:</b>	
Task # 1130: Need to figure out if we want to configure tomcat to accept \ in a URI	<b>Closed</b>
Task # 1131: Need to figure out how to enable \ (%5C) in tomcat URIs	<b>Closed</b>

#### History

##### #1 - 2010-12-03 17:58 - Rob Nahf

- Position set to 1
- Target version set to Sprint-2010.49
- Position deleted (1)

##### #2 - 2010-12-13 18:33 - Dave Vieglais

- Target version changed from Sprint-2010.49 to Sprint-2010.50
- Position deleted (11)
- Position set to 2

##### #3 - 2010-12-14 19:59 - Rob Nahf

- Status changed from New to Closed

configured tomcat to handle escaped backslashes. It might be prudent to check the security hole through a test, to see if it's something we now have to worry about. A separate story will be created for that.