# Infrastructure - Bug #1350

## metacat and libclient_java still use 'obsoletedGuid' as a MMP part name

2011-02-14 22:04 - Rob Nahf

| | | | |
|---|---|---|---|
| **Status:** | Closed | **Start date:** | |
| **Priority:** | Normal | **Due date:** | |
| **Assignee:** | Rob Nahf | **% Done:** | 100% |
| **Category:** | | **Estimated time:** | 0.00 hour |
| **Target version:** | Sprint-2011.12-Block.2 | | |
| **Milestone:** | | **Story Points:** | |
| **Product Version:** | * | | |

**Description**

The spec uses obsoletedPid, as does gmn.
Update after the demo.

**Subtasks:**

| | |
|---|---|
| Task # 1351: update MNode.java to use obsoletedPid | **Closed** |

### History

**#1 - 2011-03-07 17:29 - Rob Nahf**

*- Assignee set to Rob Nahf*

**#2 - 2011-03-07 18:07 - Rob Nahf**

*- Position set to 19*

**#3 - 2011-03-17 16:05 - Dave Vieglais**

*- Position set to 5*

*- Target version changed from Sprint-2011.10-Block.2 to Sprint-2011.11-Block.2*

*- Position deleted (22)*

**#4 - 2011-03-22 13:52 - Dave Vieglais**

*- Status changed from New to In Progress*

**#5 - 2011-03-22 13:59 - Dave Vieglais**

*- Position set to 4*

*- Target version changed from Sprint-2011.11-Block.2 to Sprint-2011.12-Block.2*

*- Position deleted (13)*

**#6 - 2011-03-28 15:04 - Dave Vieglais**

*- Status changed from In Progress to Closed*