Infrastructure - Bug #2446

Using Apache, Block metacat endpoints

2012-03-06 19:19 - Robert Waltz

Status:	Closed	**Start date:**	2012-05-21
Priority:	Normal	**Due date:**	
Assignee:	Robert Waltz	**% Done:**	100%
Category:	d1_cn_buildout	**Estimated time:**	0.00 hour
Target version:	Sprint-2012.21-Block.3.3		
Milestone:	CCI-1.0.0	**Story Points:**	
Product Version:	*		

Description

We need to disallow access to the native Metacat interface on the CNs as well as the Metacat MN implementation rest endpoints.

In apache, block assess to knb/metacat, knb/servlet/metacat and knb/d1/mn

Creation of the document OBJECT_FORMAT_LIST.1.1 still needs to happen via the native knb interface at initial environment population. So the insert method must still be accessible from localhost:8080 calls.

knb/admin must remain open

Subtasks:

Task # 2791: verify on dev machines **New**

History

#1 - 2012-03-16 02:33 - Dave Vieglais

- Position set to 1

- Target version changed from Sprint-2012.09-Block.2.1 to Sprint-2012.11-Block.2.2

#2 - 2012-04-23 16:35 - Dave Vieglais

- Target version changed from Sprint-2012.11-Block.2.2 to Sprint-2012.17-Block.3.1

- Position set to 4

- Position deleted (27)

#3 - 2012-05-07 17:15 - Dave Vieglais

- Position deleted (14)

- Target version changed from Sprint-2012.17-Block.3.1 to Sprint-2012.19-Block.3.2

- Position set to 5

#4 - 2012-05-11 02:22 - Robert Waltz

- Status changed from New to In Progress

#5 - 2012-05-30 12:30 - Dave Vieglais

- Position set to 1

- Position deleted (16)

- Target version changed from Sprint-2012.19-Block.3.2 to Sprint-2012.21-Block.3.3

#6 - 2012-06-07 15:58 - Robert Waltz

- Status changed from In Progress to Closed