

Infrastructure - Task #2646

Story # 1906 (Closed): Review, revise, and update architecture documentation

MNReplication.getReplica() - Add information about CNReplication.isNodeAuthorized()

2012-04-26 00:28 - Roger Dahl

<b>Status:</b>	New	<b>Start date:</b>	2012-04-26
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>	Dave Vieglais	<b>% Done:</b>	0%
<b>Category:</b>	Documentation	<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	Maintenance Backlog	<b>Story Points:</b>	
<b>Milestone:</b>	CCI-1.0.0		
<b>Product Version:</b>	*		
<b>Description</b>			
Add information about the MN being required to call CNReplication.isNodeAuthorized().			
Also, someone (Rob?) brought up a good point that an MN is free to use a whitelist instead. Could be handy if it accepts replicas only from specific MNs and fully trusts those MNs.			
Actually, it was Chris. From our discussion:			
So, if that is your only criteria and you fully trust the target MN, then it should be ok to just use the NodeReplicationPolicy as a whitelist.			

History

#1 - 2014-10-02 17:21 - Dave Vieglais

- Target version set to Maintenance Backlog