

## Infrastructure - Task #2750

Bug # 2744 (Closed): CNode client does not respect Session param

### add D1Client.getCN(Session session) method

2012-05-11 17:27 - Rob Nahf

<b>Status:</b>	Closed	<b>Start date:</b>	2012-05-11
<b>Priority:</b>	High	<b>Due date:</b>	
<b>Assignee:</b>	Rob Nahf	<b>% Done:</b>	100%
<b>Category:</b>	d1_libclient_java	<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	Sprint-2012.19-Block.3.2	<b>Story Points:</b>	
<b>Milestone:</b>	CCI-1.0.0		
<b>Product Version:</b>	*		
<b>Description</b>			
to implement new behavior of setting the the session outside the method calls.			
Will need to take into account the singleton pattern D1Client employs.			
<b>Related issues:</b>			
Related to Infrastructure - Bug #7642: D1Client.getCN(Session s) method doesn't use the session added			<b>Closed</b> <b>2016-02-12</b>

### History

#### #1 - 2012-05-11 19:56 - Rob Nahf

- Status changed from New to Closed
- Priority changed from Urgent to High
- Target version set to Sprint-2012.19-Block.3.2
- % Done changed from 0 to 100

added a new accessor that sets the session.

#### #2 - 2016-02-12 21:26 - Rob Nahf

- Related to Bug #7642: D1Client.getCN(Session s) method doesn't use the session added