

## Infrastructure - Task #3665

### Use independent service for debian configuration information

2013-03-15 17:06 - Robert Waltz

<b>Status:</b>	Closed	<b>Start date:</b>	2013-03-15
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>	Robert Waltz	<b>% Done:</b>	100%
<b>Category:</b>	d1_cn_buildout	<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	2013.22-Block.3.3	<b>Story Points:</b>	
<b>Milestone:</b>	CCI-1.1.2		
<b>Product Version:</b>	*		

#### Description

The debian configuration relies upon property files that are included in the dataone-cn-os-core debian package. The configuration information should be published through an independent service, a web endpoint, ldap service or other database. This will allow us to update existing installations by running dpkg-reconfigure instead of having to re-install a new package to the servers, esp for recognizing new machines in an environment

#### History

##### #1 - 2013-06-05 05:00 - Robert Waltz

- Status changed from New to In Progress
- Target version changed from 2013.14-Block.2.3 to 2013.22-Block.3.3

##### #2 - 2013-07-25 16:36 - Robert Waltz

- Status changed from In Progress to Closed
- translation missing: en.field\_remaining\_hours set to 0.0