

Infrastructure - Task #7583

MNPackage.getPackage requires resource map id to download entire package

2016-01-11 23:03 - Peter Slaughter

Status:	Closed	Start date:	2016-01-11
Priority:	Normal	Due date:	
Assignee:	Jing Tao	% Done:	100%
Category:		Estimated time:	0.00 hour
Target version:		Story Points:	
Milestone:	None		
Product Version:	*		

Description

The documentation for this service, located at https://jenkins-ucsb-1.dataone.org/job/API%20Documentation%20-%20trunk/ws/api-documentation/build/html//apis/MN_APIs.html#MNPackage.getPackage indicates that the pid for any object belonging to the package can be specified, and the entire package will be downloaded. The attached script gives an example of when this is not the case. Specifying a science object results in a Bagit file with just the science object; specifying the metadata object results in a Bagit file with just the metadata object. However, when the resource map id is specified, the entire package is downloaded.

History

#1 - 2016-01-20 17:32 - Jing Tao

- Status changed from New to In Progress
- % Done changed from 0 to 30

I talked with Peter about this issue. He agrees that we can change the documentation stating that the pid should be a resource map object. If it is not resource map object, an InvalidRequest exception will be thrown.

#2 - 2016-01-26 16:49 - Jing Tao

- Status changed from In Progress to Closed
- % Done changed from 30 to 100
- translation missing: en.field_remaining_hours set to 0.0

I did the change on the code and also modified the documenation

Files

testGetPackage.sh	378 Bytes	2016-01-11	Peter Slaughter
-------------------	-----------	------------	-----------------