

Infrastructure - Bug #8834

CNCore.reserveldentifier documentation correction

2019-08-09 17:43 - Lauren Walker

Status:	Closed	Start date:	2019-08-09
Priority:	Normal	Due date:	
Assignee:	Dave Vieglais	% Done:	100%
Category:	Documentation	Estimated time:	0.00 hour
Target version:		Story Points:	
Milestone:	None		
Product Version:	*		

Description

The documentation for `CNCore.reserveldentifier()` states that an `id` data parameter should be sent, but it should be `pid`.

```
curl -H "Authorization: Bearer $token" -F "id=urn:uuid:56daae54-a42a-4927-83f1-878ec25ac366" -X POST https://cn.dataone.org/cn/v2/reserve
```

results in:

```
<error detailCode="4210" errorCode="409" name="IdentifierNotUnique">
  <description>The given identifier is already in use: null</description>
</error>
```

but

```
curl -H "Authorization: Bearer $token" -F "pid=urn:uuid:56daae54-a42a-4927-83f1-878ec25ac366" -X POST https://cn.dataone.org/cn/v2/reserve
```

works:

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?><identifier xmlns="
http://ns.dataone.org/service/types/v1">urn:uuid:56daae54-a42a-4927-83f1-878ec25ac366</identifier>
```

On a related note, the documentation for [CNCore.generateIdentifier\(\)](#) doesn't mention that the identifier is also reserved, but that seems to be the case. Robyn Thiessen-Bock and I were incorporating these APIs into MetacatUI today, and that was helpful information that we wished were in the documentation.

History

#1 - 2019-09-18 20:27 - Dave Vieglais

- % Done changed from 0 to 100
- Assignee set to Dave Vieglais
- Status changed from New to Closed

Fixed in docs dev branch